

## CAR 1122 - 1130 - 1155 BAG ICLEAN MODELS



### MOTORISATION

Motorised industrial vacuum cleaner with single-phase or three-phase side channel turbine, of our production and made in die cast aluminium. Extremely sturdy, silent, powerful and reliable and suitable for continuous use 24 hours a day.

### CAR 1122 - CAR 1130 ICLEAN MODELS

With single stage single-phase or 3-phase turbine

### CAR 1155 P - CAR 1155 S ICLEAN MODELS

With dual stage 3-phase turbine. CAR 1155 P for greater air flow rate CAR 1155 S for greater vacuum

### ICLEAN AUTOMATIC CLEANING OF FILTERS

The models equipped with the ICLEAN cleaning system guarantee constant suction, ensuring the cleanliness of the filters without any intervention from the operator and without interrupting operation as the filters are periodically cleaned by the vibrating action. These models have been designed to meet the requirements of continuous and extended vacuum cleaning, being particularly suitable when they are coupled with machines in operation

### FILTERING SYSTEM

The external part of the filter is made using conductive material, a property that allows discharge of the electrostatic current generated during vacuum cleaning.

The internal part, thanks to the use of the HEPA filter, is able to filter 99.995% of dust with 0.3 μ particles, making the work environment safer and free of dust.

The filters are contained in stainless steel cylinders that serve as protection against sucked materials that might be corrosive or abrasive..

### OPERATION

The cyclic cleaning of the filters occurs every 3 minutes by cleaning in alternating phases each of the mounted filters for 1.5 seconds, closing the aspiration and thus facilitating their cleaning by means of the vibration and the blowing provided independently from the machine without using the on-board compressor.

The suction is always present even during the cyclic cleaning phase of the filters.

### LONGOPAC®, THE CONTINUOUS BAG FOR COLLECTING DUST MORE SAFELY

The LONGOPAC® system uses a special continuous bag consisting of a very resistant plastic tube that is 20 metres long and placed under the collection hopper. The principal feature of this system is that the amount of waste determines the size and weight of the bag which can be sealed and easily transported and disposed of without contaminating the working environment, avoiding direct contact with the vacuumed material that occurs with conventional drums and the consequent dispersion of dust in the environment and inhalation by the operator.

MODEL	MOTOR	POWER	VOLTAGE	FILTER SHAKER	FILTERING CLASS	AIR FLOW RATE	DEPRESSION	DEPRESSION	COLLECTING SYSTEM	DIMENSIONS	WEIGHT	PRICE
<i>VERSIONS WITH FILTER CLEANING BY VIBRATION AND BLOWING ENGINE ON BOARD</i>												
CAR 1122 BAG ICLEAN	Turbine	2.2 KW	230 V/ 50Hz	Automatic		320 m3/h	VALVE 260 mBar	MAX 320 mBar	LONGOPAC®	115x65cm h160cm	197 Kg	
CAR 1130 BAG ICLEAN	Turbine	3 KW	400V 3P+N+E 50Hz	Automatic		320 m3/h	VALVE 260 mBar	MAX 320 mBar	LONGOPAC®	115x65cm h160cm	197 Kg	
CAR 1155 P BAG ICLEAN	Turbine + Air flow	5.5 KW	400V 3P+N+E 50Hz	Automatic		560 m3/h	VALVE 260 mBar	MAX 320 mBar	LONGOPAC®	115x65cm h160cm	222 Kg	
CAR 1155 S BAG ICLEAN	Turbine + Depression	5.5 KW	400V 3P+N+E 50Hz	Automatic		380 m3/h	VALVE 460 mBar	MAX 500 mBar	LONGOPAC®	115x65cm h160cm	222 Kg	

### VERSIONS WITH DIFFERENT VOLTAGES ARE AVAILABLE UPON REQUEST

### *VERSIONS WITH FILTER CLEANING BY VIBRATION AND COMPRESSED AIR SUPPLY*

CAR 1100 BAG I CLEAN + AIR MODELS The machine is provided with coupling for the connection of the line compressor. Recommended for machines with a fixed location and for connection to machines in operation

SPARE PARTS	DESCRIPTION	PRICE
LONGOPAC®	1 cartridge of 20 metres complete with cable ties	
	LONGOPAC® pack with 4 cartridges of 20 metres	

### *STAINLESS STEEL VERSIONS*

MOD. CAR 1100 BAG ICLEAN + STAINLESS STEEL The STAINLESS STEEL versions include the cover, filter chamber and bin in STAINLESS STEEL AISI 304

OPTIONAL	DESCRIPTION	PRICE
REMOTE CONTROL	Remote start the vacuum cleaner for use in centralised plants	

CODE	RECOMMENDED KIT	Ø mm	PRICE
K50COA	Conductive kit for the suction of dust	50	