



## 222 ICLEAN ULTRA Classe H

MOTORIZATION

**Nr 2 Collector  
motor**

MATERIAL TO VACUUM

**Very fine dust**

FILTER TYPE

**2x Cartridge**

FILTER CLEANING

**Automatic  
Cleaning**

The 222 ICLEAN ULTRA model was developed as an evolution of the 235 ICLEAN model. The advantages in terms of suction performance are obvious, but above all the percentage of filtration of the sucked material is absolute, representing further safety for operators thanks to the installation of 2 HEPA D.O.P. secondary filters. The renewal of the design with the installation of the motors in the lower rear part allowed the lowering of the machine, facilitating its transport. The center of gravity in the lower part makes the machine stable when moving. The vacuum cleaner is able to intervene autonomously to restore the original filtering capacity.

## Features

	<p><b>CERTIFICATION</b> Available class H certification</p>		<p><b>EXTRA FILTRATION</b> 2 ULPA 15 certified secondary filters</p>
	<p><b>CLEANING SYSTEM</b> ICLEAN patented cleaning system</p>		<p><b>EMPTYING</b> Longopack bag 45 metres</p>
	<p><b>FILTRATION</b> HEPA+PTFE cartridge filter</p>		<p><b>ENGINE</b> 2 By-pass motors</p>

## Technical specifications

Technical data	222 ICLEAN ULTRA Classe H
MATERIAL TO VACUUM	Very fine dust
MOTORIZATION	Nr 2 Collector motor
MARKING	H Class - IEC 60335-2-69:2016 – ANNEX AA
POWER	2200 W
VOLTAGE	230 V
FREQUENCY	50 / 60 Hz
AMPERAGE	9,6 A
AIR CONSUMPTION	-
AIRFLOW	340 m3/h
DEPRESSION	230 mBar
MAX DEPRESSION	-
SUCTION INLET	Type B Tang. 60 mm
DIMENSIONS	80x53 h118 cm
WEIGHT	67
COLLECTION SYSTEM	Longopac®
COLLECTION CAPACITY	Longopac® 22 mt
LONGOPAC	-
ELECTRIC FLOATER	-
FILTER CHAMBER DIAMETER	Ø 370 mm
FILTER TYPE	2x Cartridge
FILTERING MEDIA AND PROPERTIES	HEPA + PTFE IEC 60335-2-69:2016 – ANNEX AA
FILTER SURFACE	11.000 cm <sup>2</sup>
FILTER CLEANING	Automatic Cleaning
LIQUID EMPTYING	-
FILTER HEPA	Secondary Filters H14 with 99,995% MPPS 0,12 µm
HEPA FILTERING SURFACE	2x Filter - 19.000 cm <sup>2</sup>