

BF

MOTORIZATION

Turbine

MATERIAL TO VACUUM

Dust

FILTER TYPE

Cartridge


FILTER CLEANING

Manual Shaking

The BF 22 and BF 3 models are Coynco's most compact single-phase or three-phase turbine vacuum cleaners while also being highly modular and suitable for coupling with OEM machines and production lines. Designed for 24/7 continuous operation with zero maintenance, they optimize production processes. The filtration system includes a conductive, aluminized M-class cartridge filter, washable and protected by a patented stainless steel chamber. The machine is equipped with a manual filter cleaning system featuring an integrated shaking mechanism.



Features



ENGINE
2,2 or 3 kW Turbine



24/7
Suitable for continuous work



SUCTION
Central inlet Ø 50mm



EMPTYING
Collection system with 12 lt



FILTRATION
Conductive M Cartridge Filter



CLEANING SYSTEM
Manual shaking cleaning system



24/7
Suitable for continuous work

Technical specifications

Technical data	BF 22	BF 3
MATERIAL TO VACUUM	Dust	Dust
MOTORIZATION	Turbine	Turbine
MARKING	-	-
POWER	2,2 kW	3 kW
VOLTAGE	230 V	400 V
FREQUENCY	50 / 60 Hz	50 / 60 Hz
AMPERAGE	16 A	6,7 A
AIR CONSUMPTION	-	-
AIRFLOW	320 m3/h	320 m3/h
DEPRESSION	300 mBar	320 mBar
MAX DEPRESSION	220 mBar	250 mBar
SUCTION INLET	Type F Cent. 50 mm	Type F Cent. 50 mm
DIMENSIONS	83x51 h50 cm	83x51 h50 cm
WEIGHT	49 Kg	49 Kg
COLLECTION SYSTEM	-	-
COLLECTION CAPACITY	12 L	12 L
LONGOPAC	-	-
ELECTRIC FLOATER	-	-
FILTER CHAMBER DIAMETER	Ø 370mm	Ø 370mm
FILTER TYPE	Cartridge	Cartridge
FILTERING MEDIA AND PROPERTIES	M Conductive Aluminized	M Conductive Aluminized
FILTER SURFACE	4.800 cm2	4.800 cm2
FILTER CLEANING	Manual Shaking	Manual Shaking
LIQUID EMPTYING	-	-
FILTER HEPA	-	-
HEPA FILTERING SURFACE	-	-