

BT / WT 75 BASIC ATEX 21



MOTORIZATION

Turbine

MATERIAL TO VACUUM

Dust and liquids

FILTER TYPE


Star Polyester

FILTER CLEANING

Manual Shaking

Industrial vacuum cleaners WT 75 and BT 75 are the most popular turbine models as they enjoy excellent reliability thanks to the side channel turbine and are multipurpose for suction of any kind of debris but not recommended for fine dust. Their simplicity and versatility make them among the most popular models on the market.

Features



SAFETY
Thermal magnetic circuit breaker



EMPTYING
Collection system with 75L tank



ENGINE
2,2 - 3 - 4 KW Turbine available



PULIZIA FILTRO
Filtro in poliestere + HEPA
(opzionale)

Technical specifications

Technical data	BT 754 BASIC ATEX 21	WT 754 BASIC ATEX 21
MATERIAL TO VACUUM	Dust and liquids	Dust and liquids
MOTORIZATION	Turbine	Turbine
MARKING	Zone 20/21 - II 2D Ex h tb IIIC T135°C Db IP64	Zone 20/21 - II 2D Ex h tb IIIC T135°C Db IP64
POWER	3,4 kW	3,4 kW
VOLTAGE	400 V - 50 Hz	400 V - 50 Hz
FREQUENCY	50 / 60 Hz	50 / 60 Hz
AMPERAGE	8,9 A	8,9 A
AIR CONSUMPTION	-	-
AIRFLOW	320m ³ /h 50 Hz 405m ³ /h 60 Hz	320m ³ /h 50 Hz 405m ³ /h 60 Hz
DEPRESSION	320 mBar – 50 Hz 380 mBar - 60 Hz	320 mBar – 50 Hz 380 mBar - 60 Hz
MAX DEPRESSION	220 mBar	220 mBar
SUCTION INLET	Type B Tang. 60 mm	Type C Centr. 70 mm
DIMENSIONS	80x60 h154 cm	80x60 h154 cm
WEIGHT	100 Kg	100 Kg
COLLECTION SYSTEM	Barrel	Barrel
COLLECTION CAPACITY	75 L	75 L
LONGOPAC	-	-
ELECTRIC FLOATER	-	-
FILTER CHAMBER DIAMETER	Ø 460mm	Ø 460mm
FILTER TYPE	Star Polyester	Star Polyester
FILTERING MEDIA AND PROPERTIES	M Antistatic	M Antistatic
FILTER SURFACE	20.000 cm ² - 30.000 cm ² Opt	20.000 cm ² - 30.000 cm ² Opt
FILTER CLEANING	Manual Shaking	Manual Shaking
LIQUID EMPTYING	-	-
FILTER HEPA	Optional	Optional
HEPA FILTERING SURFACE	-	-