

DTX 1500 BASIC ATEX 2-22



MOTORIZATION

Centrifugal Fan

MATERIAL TO VACUUM

Suspension dust

FILTER TYPE

Star Polyester

FILTER CLEANING


**Manual
Shaking/SemiAuto
Optional**

DTX 1500 BASIC ATEX model is a dust collector equipped with a 2.2 kW centrifugal fan and a stellar polyester filter; it is suitable for use in environments with a potentially explosive atmosphere, is characterised by a high air flow rate and low depression. It is suitable for all environments where suspended airborne dust is present.


Features



COLLECTION
Collection system with 50L tank



SAFETY
Thermal magnetic circuit breaker



ENGINE
2,2 KW Centrifugal fan



PULIZIA FILTRO
Filtro in poliestere + HEPA
(opzionale)

Technical specifications

Technical data	DTX 1500 BASIC ATEX 2-22
MATERIAL TO VACUUM	Suspension dust
MOTORIZATION	Centrifugal Fan
MARKING	Zone 20/22 - II 3G Ex dc h IIB T3 Gc II 3D Ex h tc IIIC T 135°C Dc IP65
POWER	2,2 kW
VOLTAGE	400 V
FREQUENCY	50 Hz
AMPERAGE	6A
AIR CONSUMPTION	-
AIRFLOW	1.500 m3/h
DEPRESSION	34 mBar
MAX DEPRESSION	-
SUCTION INLET	Type E Tang. 120mm
DIMENSIONS	80x66 h168 cm
WEIGHT	85 Kg
COLLECTION SYSTEM	Barrel
COLLECTION CAPACITY	50 L
LONGOPAC	-
ELECTRIC FLOATER	-
FILTER CHAMBER DIAMETER	Ø 460mm
FILTER TYPE	Star Polyester
FILTERING MEDIA AND PROPERTIES	M Conductive Aluminized
FILTER SURFACE	30.000 cm2
FILTER CLEANING	Manual Shaking/SemiAuto Optional
LIQUID EMPTYING	-
FILTER HEPA	Optional
HEPA FILTERING SURFACE	-