



FLX

MOTORIZATION

Turbine

MATERIAL TO VACUUM

Welding flux

FILTER TYPE


Star Polyester

FILTER CLEANING

Manual Shaking

The FLX 15 model is a robust and powerful industrial vacuum cleaner, ideal for the suction of light materials such as plastic, textiles, and paper trimmings. Equipped with a 1.5 kW turbine and operating at 400 V / 50 Hz, it delivers an airflow of 220 m³/h and a vacuum of 200 mBar, ensuring high performance. The antistatic polyester star filter, with a filtering surface of 13,000 cm², provides efficient material filtration. The machine includes a manual filter cleaning system and a 100 mm butterfly discharge for quick and easy emptying of the 50-liter tank. With its solid structure and significant dimensions (55 x 95 x h155 cm), it is designed for demanding industrial applications.

Features




ENGINE
1,5 kW Turbine



24/7
Suitable for continuous work



SUCTION
Central inlet Ø 50mm



EMPTYING
Butterfly valve outlet Ø 100 mm



FILTRATION
L anti-static polyester star filter



CLEANING SYSTEM
Manual shaking cleaning system

Technical specifications

Technical data	FLX 15
MATERIAL TO VACUUM	Welding flux
MOTORIZATION	Turbine
MARKING	-
POWER	1,5 kW
VOLTAGE	400 V
FREQUENCY	50 Hz
AMPERAGE	-
AIR CONSUMPTION	-
AIRFLOW	220 m3/h
DEPRESSION	200 mBar
MAX DEPRESSION	-
SUCTION INLET	Type F Cent. 50 mm
DIMENSIONS	55x95 h155 cm
WEIGHT	75 Kg
COLLECTION SYSTEM	-
COLLECTION CAPACITY	50 L
LONGOPAC	-
ELECTRIC FLOATER	-
FILTER CHAMBER DIAMETER	Ø 400 mm
FILTER TYPE	Star Polyester
FILTERING MEDIA AND PROPERTIES	L Antistatic
FILTER SURFACE	13.000 cm2
FILTER CLEANING	Manual Shaking
LIQUID EMPTYING	-
FILTER HEPA	-
HEPA FILTERING SURFACE	-