



S-2M / S-2M BAG ICLEAN

MOTORIZATION

**Nr 2 Collector
motor**

MATERIAL TO VACUUM

Very fine dust

FILTER TYPE

2x Cartridge

FILTER CLEANING

**Automatic
Cleaning**

S2M ICLEAN is a 235 ICLEAN 2-motor direct derivation cleaner, strengthened with a new trolley and with characteristics of great versatility and ease of use. Among the 2-motor vacuum cleaners, it is the most effective for vacuuming fine dust, where it stands out for its reliability, confirming itself as one of the best products on the market.

Features



CLEANING SYSTEM
ICLEAN patented cleaning system



ENGINE
2 By-pass motors



POWERTOOLS
Powertool available



KIT LIFT
Lifting system with gas springs



EMPTYING
Collection system with 45l barrel



FILTRATION
2 conductive HEPA + PTFE
cartridge filters

Technical specifications

Technical data	S2M ICLEAN	S-2M BAG ICLEAN	S-2M BAG ICLEAN CLASSE H
MATERIAL TO VACUUM	Very fine dust	Very fine dust	Very fine dust
MOTORIZATION	Nr 2 Collector motor	Nr 2 Collector motor	Nr 2 Collector motor
MARKING	-	-	H Class - IEC 60335-2-69:2016 – ANNEX AA
POWER	2200 W	2200 W	2200 W
VOLTAGE	230 V	230 V	230 V
FREQUENCY	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
AMPERAGE	9,6 A	9,6 A	9,6 A
AIR CONSUMPTION	-	-	-
AIRFLOW	340 m3/h	340 m3/h	340 m3/h
DEPRESSION	230 mBar	230 mBar	230 mBar
MAX DEPRESSION	-	-	-
SUCTION INLET	Type B Tang. 60 mm	Type B Tang. 60 mm	Type B Tang. 60 mm
DIMENSIONS	70x50 h123 cm	48x91 h138 cm	48x91 h138 cm
WEIGHT	55	62	62
COLLECTION SYSTEM	Barrel	Longopac®	Longopac®
COLLECTION CAPACITY	45 L	Longopac® 22 mt	Longopac® 22 mt
LONGOPAC	Si	Si	Si
ELECTRIC FLOATER	-	-	-
FILTER CHAMBER DIAMETER	Ø 370 mm	Ø 370 mm	Ø 370 mm
FILTER TYPE	2x Cartridge	2x Cartridge	2x Cartridge
FILTERING MEDIA AND PROPERTIES	HEPA + PTFE	HEPA + PTFE	HEPA + PTFE IEC 60335-2-69:2016 – ANNEX AA
FILTER SURFACE	8.000 cm2	8.000 cm2	8.000 cm2
FILTER CLEANING	Automatic Cleaning	Automatic Cleaning	Automatic Cleaning
LIQUID EMPTYING	-	-	-
FILTER HEPA	Opzionale - Secondary filters H14 with 99,995% MPPS 0,12 µm	Opzionale - Secondary filters H14 with 99,995% MPPS 0,12 µm	Opzionale - Secondary filters H14 with 99,995% MPPS 0,12 µm
HEPA FILTERING SURFACE	Optional - 2x Cartridge ULPA+PTFE 22.400 cm2	Optional - 2x Cartridge ULPA+PTFE 22.400 cm2	Optional - 2x Cartridge ULPA+PTFE 22.400 cm2