

# S-3MB / S-3MW BASIC



MOTORIZATION

**Nr 3 Collector motor**

MATERIAL TO VACUUM

**Dust and liquids**

FILTER TYPE

**Star Polyester**

FILTER CLEANING

**Manual Shaking**

S-3MB / S-3MW BASIC are modular industrial vacuum cleaners designed for the extraction of dust, solids, and liquids in production environments and workshops. Equipped with three powerful by-pass motors with 3300 W, they deliver an airflow rate of up to 510 m<sup>3</sup>/h and optimal filtration thanks to the polyester star filter with a surface area of up to 30,000 cm<sup>2</sup>. The quick-release collection system, available with 75-liter containers or Longopac® bags, ensures ease of use and fast waste disposal. Ideal for those seeking high performance and versatility.

## Features



ENGINE  
**3 By-pass motors**



LIQUID LEVEL  
**Magnetic connection (OPTIONAL)**



COLLECTION  
**Separate chip bucket (optional)**



FILTRATION  
**Primary stellar polyester filter**

## Technical specifications

Technical data	S-3MW L BASIC	S-3MW L + EFLT	S-3MB L BASIC	S-3MB XM BAG ECO BASIC
MATERIAL TO VACUUM	Dust and liquids	Dust and liquids	Dust and liquids	Dust
MOTORIZATION	Nr 3 Collector motor	Nr 3 Collector motor	Nr 3 Collector motor	Nr 3 Collector motor
MARKING	-	-	-	-
POWER	3300 W	3300 W	3300 W	3300 W
VOLTAGE	230 V	230 V	230 V	230 V
FREQUENCY	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
AMPERAGE	14,4 A	14,4 A	14,4 A	14,4 A
AIR CONSUMPTION	-	-	-	-
AIRFLOW	510 m3/h	510 m3/h	510 m3/h	510 m3/h
DEPRESSION	230 mBar	230 mBar	230 mBar	230 mBar
MAX DEPRESSION	-	-	-	-
SUCTION INLET	Type C Cent. 70 mm	Type C Cent. 70 mm	Type B Tang. 60 mm	Type B Tang. 60 mm
DIMENSIONS	80x66 h170 cm	80x66 h170 cm	80x66 h170 cm	80x66 h170 cm
WEIGHT	70	70	70	80
COLLECTION SYSTEM	Barrel / Longopac®	Barrel / Longopac®	Barrel / Longopac®	Longopac®
COLLECTION CAPACITY	100 L / Longopac®	100 L / Longopac®	100 L / Longopac®	Longopac® 22 mt
LONGOPAC	Si	Si	Si	No
ELECTRIC FLOATER	Optional	Optional	Optional	Optional
FILTER CHAMBER DIAMETER	Ø 460mm	Ø 460mm	Ø 460mm	Ø 460mm
FILTER TYPE	Star Polyester	Star Polyester	Star Polyester	Star Polyester
FILTERING MEDIA AND PROPERTIES	L Antistatic	L Antistatic	L Antistatic	M Antistatic
FILTER SURFACE	20.000 cm <sup>2</sup> - 30.000 cm <sup>2</sup> Opt	20.000 cm <sup>2</sup> - 30.000 cm <sup>2</sup> Opt	20.000 cm <sup>2</sup> - 30.000 cm <sup>2</sup> Opt	30.000 cm <sup>2</sup>
FILTER CLEANING	Manual Shaking	Manual Shaking	Manual Shaking	Manual Shaking
LIQUID EMPTYING	-	-	-	-
FILTER HEPA	Optional H13 with 99,95% MPPS 0,12 µm	Optional H13 with 99,95% MPPS 0,12 µm	Optional H13 with 99,95% MPPS 0,12 µm	Optional H13 with 99,95% MPPS 0,12 µm
HEPA FILTERING SURFACE	-	-	-	-