



SLURRY 245 PUMP

MOTORIZATION

Nr 2 Collector motor

MATERIAL TO VACUUM

Liquids and Slurries

FILTER TYPE

Cartridge

FILTER CLEANING

No

SLURRY 245 PUMP is a versatile industrial vacuum cleaner designed for handling liquids and slurries in demanding environments. Equipped with two by-pass motors with 2200 W, it ensures an airflow rate of 340 m³/h and a vacuum pressure of 230 mBar. The collection system includes a 20-liter filter bag for slurries and a 40-liter container for liquids, featuring an integrated pump capable of discharging up to 220 liters per minute. Ideal for professional applications, it combines high performance with a robust and user-friendly design.

Features



ENGINE
2 By-pass motors



TILTING TANK
Tilting tank and scratch-resistant wheels



DRAIN HOSE
Integrated exhaust



INTEGRATED PUMP
Quick and efficient

Technical specifications

Technical data	SLURRY 245 PUMP
MATERIAL TO VACUUM	Liquids and Slurries
MOTORIZATION	Nr 2 Collector motor
MARKING	Slurry Filtration Grade - Tnt/Polycarbonate
POWER	2200 W
VOLTAGE	230 V
FREQUENCY	50 / 60 Hz
AMPERAGE	9,6 A
AIR CONSUMPTION	-
AIRFLOW	340 m3/h
DEPRESSION	230 mBar
MAX DEPRESSION	-
SUCTION INLET	Type F Cent. 50 mm
DIMENSIONS	65x56 h120cm
WEIGHT	39
COLLECTION SYSTEM	Filtering bag
COLLECTION CAPACITY	Slurries 20 L Liquids 40 L
LONGOPAC	-
ELECTRIC FLOATER	Included - Automatic Shutdown and Automatic Startup
FILTER CHAMBER DIAMETER	Ø 400 mm
FILTER TYPE	Cartridge
FILTERING MEDIA AND PROPERTIES	Submersible pump + polycarbonate filter
FILTER SURFACE	3.000 cm2
FILTER CLEANING	No
LIQUID EMPTYING	-
FILTER HEPA	-
HEPA FILTERING SURFACE	-